

TotalSense Series IAQ/Occupancy Sensor

Industry's first IAQ sensor with PIR motion detection
 Ten environmental sensors: PIR, PMx, VOC, CO2, CO, O3, RH, T, ambient light, barometric pressure
 BACnet/Modbus or analog outputs with set-point relay
 Pair with an IOTBuddy for BACnet IP or IOT Connection



DESCRIPTION

The TotalSense Series provides more data for more advanced ventilation control while drastically reducing installation cost and time on a project. It includes a comprehensive selection of IAQ sensing with carbon dioxide (CO2), relative humidity (RH), and temperature plus options for occupancy detection (PIR), total volatile organic compounds (TVOC), particulate matter (PM), Carbon Monoxide (CO), and ambient light. More than an IAQ sensor, it's the first fully configurable Indoor Environmental Quality (IEQ) sensor matrix. Motion detection (PIR) can initiate ventilation upon occupancy, providing air exchanges the instant people are present, allowing for cleaner and safer indoor spaces while still saving energy.

APPLICATIONS


- Verify effectiveness of IAQ strategies in post covid environment
- Energy management/building control
- Facilitates compliance with ASHRAE 62.1 standard for air quality
- Contributes toward satisfying Feature A08 and T06 under the WELL Building Standard®



Display, AQ ring, and standard designs



PIR Motion Detection (optional) - Detect occupancy for quicker and safer ventilation




Configure up to ten sensors

TAMPER PROOF



Tamper proof push-in lock tabs - great for schools!



NEW! PID control - program any analog output for local control of dampers or valves




RESET monitors are tested and certified for your RESET Air Projects.


FEATURES

- NEW! Save even more using an analog output for local PID control
- NEW! Dual BACnet/Modbus PLUS analog output version for BAS connection plus local analog control
- NEW! Configure quickly with the [SenvaSync](#) app
- Specify the exact product for your application with made in USA quality
- NEW! Use PIR occupancy sensor to enable auto-wakeup of display
- Initiate ventilation immediately upon occupancy detection for healthier buildings and energy savings
- Sense unhealthy or offensive air with TVOC
- Detect a variety of PM sizes to indicate airborne respiratory droplets, allergens, and other dangers
- Industry-leading temperature and barometric pressure compensated CO2 sensing with non-dispersive infrared sensing element (NDIR), 15+ year life expectancy on CO2 sensing element; $\pm 30\text{ppm}$, $\pm 3\%$ of reading
- Capacitive touch buttons make setup and use simple
- Slim and sleek surface-mount enclosure is tamper-proof and easy to install
- Field-replaceable PM, RH, Temp, and CO2 sensors ease maintenance
- Set-point sliders and pushbuttons are also available to meet the requirements for any job
- 7-year limited warranty / 3 years on CO2 sensor - 2 years on all others


TEN SENSING TECHNOLOGIES



DIMENSIONS



Standard Surface Mount



Concealing Ring (Provided)

- Conceal oversized drywall cutouts or European junction boxes

Warning: The datasheet is designed for reference only. Refer to installation instructions that accompany the product and heed all safety instructions. Product improvement is a continuing process at Senva. Changes may occur to products without prior notice.

SPECIFICATIONS

Power Supply	Non-Display	16-30VDC/24VAC ⁽¹⁾ , 3.5W nominal, 4W max.
	Display or LED Ring	16-30VDC/24VAC ⁽¹⁾ , 4.3W nominal, 5W max.
Interface	OLED (optional)	1.5" Organic LED Display, 128x128, color
	Air Quality Ring	Color changing (red/yellow/green) LED Air Quality Ring
Analog Outputs (Analog or Dual version only)	Quantity	Up to 3 outputs
	Source	CO ₂ , RH%, Temp, Temp slider, TVOC (selectable)
	Scale	0-5V, 0-10V, 4-20mA (switch selectable, programmable per output)
Protocol Output (Comms or Dual version only)	Protocol	BACnet MS/TP or Modbus RTU
	Connection	3-wire RS-485, with isolated ground
	Data Rate	9600, 19200, 38400, 57600, 76800, 115200 (switch selectable)
	Address Range	0-127
Relay (Standard except for PM models)	Type	Solid-state output, 1A @ 30VAC/DC, N.O.
	Polarity	NO/NC (selectable)
	Source	CO ₂ setpoint, RH setpoint, Temp setpoint, TVOC setpoint, PIR motion detection, Air Quality, off (selectable)
CO ₂ (Optional)	Type	Non-dispersive Infrared (NDIR)
	Accuracy	±(30ppm + 3% of reading) (400-2,000ppm), -10-50°C, 0-85%RH
		±(50ppm+ 5% of reading) (2,000-5,000ppm), -10-50°C, 0-85%RH
		>5,000ppm consult factory
	Resolution	1 ppm
	Range	0-2,000 PPM (Default) (Programmable up to 10,000ppm)
	Response time	90 seconds to 90% reading
	Sample rate	1s
Temp and Pressure Compensation	Yes, barometric pressure readable over comms	
Relative Humidity (Optional)	Type	Digital CMOS
	Accuracy(2)	2% models, +/-2% over 0 to 80%RH range

	Resolution	0.05%RH
	Response time (3)	30s
	Sample rate	3s
	Operating range	0 to 100%RH (non-condensing)
	Operating conditions (4)	-4 to 140oF (-20 to 60° C) @ RH>90%; -4 to 176oF @ RH=50%
Temperature Transmitter (Optional)	Type	Silicon Band-gap
	Nominal Accuracy	±0.3° C (operating range)
	Maximum Accuracy (2)	±0.5° C (at 25° C), ±1.0° C
	Resolution	0.1° C
	Response time	30s
	Sample rate	3s
TVOC (Optional)	Type	MOS
	Gas	Total VOC
	Formaldehyde CH ₂ O	Responsive to Formaldehyde concentrations 50-1000 ppb
	Sensitivity Range	0-10,000 µg/m ³ (Display may be programmed to show PPB)
	Response Time	<10s
	Accuracy (5)	±20 µg/m ³ + 15% at 1 to 500 µg/m ³ (typical)
	Output	0-2,000 µg/m ³ (default) programmable up to 10,000 µg/m ³
PMx (Optional)	Type	Optical
CLASS 1 LASER PRODUCT	Size Range	PM1.0, PM2.5, PM4.0, PM10.0
	Scale	0-1,000 µg/m ³
	Lower detection limit	0.3 µm
	Precision	±10 µg/m ³ (0-100µg/m ³); ±10% (100-1,000 µg/m ³)
	Long-Term Drift	±1.25 µg/m ³ / year
Carbon Monoxide	Type	Electrochemical
	Detection Range	0-200 ppm
	Accuracy	±5% FullScale @20°C
	Resolution	1 ppm
	Response Time	60 seconds
	Sensor Life	5 years
	Certifications	UL2034 Recognized Component
Ozone	Type	MOS
	Ozone Detection Range	20-500 ppb
	Accuracy	±15% of FS @ 20° C
PIR (Optional)	Type	Passive Infrared
	Axis X field of view	140o, 15 ft (4.5m)
	Axis Y field of view	76o, 15 ft (4.5m)
Ambient Light	Type	Phototransistor
	Scale	0-100 fc (lm/ft ²), readable over comms
Operating Environment	Temperature	32 to 122oF (0 to 50oC)
	Humidity	0-95% non-condensing
Enclosure	Material	ABS Plastic
	Dimensions	5.67”h x 3.00”w x 1.07”d (With concealing ring: 6.35”h x 3.69”w x 1.25”d)
Compliance	Agency	CE, RoHS
	Accreditations	RESET Air Accredited Monitor
	Standards	Facilitates compliance with ASHRAE 62.1 standard for air quality

Contributes toward satisfying Feature A08 and T06 under WELL Building Standard®

- (1) One side of transformer, secondary is connected to signal common. Dedicated transformer is recommended.
- (2) Models with PM sensor included achieve $\pm 5\%$ accuracy over 0 to 80%RH range and an additional temperature shift of up to $+0.5^\circ\text{C}$.
- (3) Time for reaching 63% of reading at 25°C and 1 m/s airflow.
- (4) Long term exposures to conditions outside normal range at high humidity may temporarily offset the RH reading ($+3\%RH$ after 60 hours).
- (5) Wiring with silicone or other high VOC insulation will affect TVOC readings.

** Product improvement is a continual process at Senva and product features and specification may change without prior notice. Refer to instructions that accompany the product for installation and wiring.*