


Fixed Series Fixed (Go/No) Current Switch

- Go/No status
- 0.25-200A range
- Split and solid core models
- N.O. 30VAC/DC or 120VAC output
- Optional command relay with LED




DESCRIPTION

Looking for cost-effective status? Our mini-solid core fits in the smallest enclosures. Our split-core is great for retrofit, plus you can snap on a serviceable command relay for controlling the load in a single device. Great for go/no status on resistive loads, unit-vent heaters, and more. NOTE: CR1 series command relay has been updated to CR3 and CR4 series.

APPLICATIONS

- Monitoring on/off status of electrical loads
- Monitoring direct-drive units, exhaust fans, and other fixed loads
- Verifying lighting run times
- Great for data center current switch sensing



Relay option available with C-2300

Run status based on current

Buy American Act Certified

FEATURES

- Solid-state—no moving parts to fail
- Less expensive than 277V relays for lighting status
- More reliable for status than relays across auxiliary contacts
- Industry leading 7 year limited warranty

ORDERING

SPLIT CORE	Range (Amps)	Max Amps	Sensor AP.	N.O. Output
C-2300	0.35A	200A	0.75"	1.0A@30VAC/DC
C-2200LV	0.25A	100A	0.75"	0.2A@120VAC


Model	Coil Current	Contact Rating	Lead Length	Coil Rating
SPLIT CORE - MINI				
C-2200	1.0A	50A	0.375"	1.0A@30VAC/DC
SOLID CORE				
C-1300	0.25A	50A	0.52"	1.0A@30VAC/DC
SOLID CORE - MINI				
C-1200	0.25A	50A	0.30"	1.0A@30VAC/DC
C-1200HV	0.75A	50A	0.30"	0.2A@120VAC
C-1200HV-240V	0.25A	50A	0.30"	1.0A@240VAC

Model	Contact rating	Coil
COMMAND RELAY - DIRECT MOUNT (MOUNTS ON ALL 2300 SERIES CURRENT DEVICES)		
CR3-24	N.O. 10A @ 125VAC	24VAC/DC 15mA nominal
CR4-24	N.C. 10A @ 125VAC	24VAC/DC 15mA nominal
CR3-12	N.O. 10A @ 125VAC	9-12VDC 30mA nominal
CR4-12	N.C. 10A @ 125VAC	9-12VDC 30mA nominal

Other coil voltages available—consult factory

DIMENSIONS

**SPLIT CORE
C-2300**



L: 2.5" H: 0.57" W: 2.23"
A: 0.75"x. 0.75"

- Mount sensor without removing conductor for installation savings
- Clamp on conductor with iris, or use detachable base to screw or DIN mount
- Larger 0.75" aperture accommodates oversized conductors

OPTIONAL RELAY



L: 0.84" H: .72" W: 2.06"

- Add to 2300 series to get start/stop/status in a single device
- Reduces the number of installed components... saves time and space
- Removable relay facilitates service

**SPLIT CORE - MINI
C-2200**



L: 2.00" H: .75" W: 1.75"
A: .040"x 0.32"

- Mount sensor without removing conductor for installation savings
- Fits in small enclosures
- Clamp on conductor with iris, or screw mount detachable base

**SOLID CORE
C-1300**



L: 2.27" H: 1.04" W: 1.6"
A: 0.52" diameter

- Compact design
- Aperture accommodates spade terminals

**SOLID CORE - MINI
C-1200**



L: 1.78" H: .88" W: 1.31"
A: 0.30" diameter

- Super small—fits anywhere
- Low cost

Warning: The datasheet is designed for reference only. Refer to installation instructions that accompany the product and heed all safety instructions. Product improvement is a continuing process at Senva. Changes may occur to products without prior notice.

SPECIFICATIONS

Standard Output Rating	1.0A@30VAC/DC
Line Voltage Output Rating	0.2A@120VAC (-HV MODELS ONLY)
Output Type	NO, solid-state FET
Environmental Rating	5-140 °F (-15-60 ° C) 10-90% RH Non-condensing
Insulation Class	600V RMS. For use on insulated conductors only!
Insulation Class	Use minimum 75 ° C insulated conductor
Sensor Power	Induced
Frequency Range	50/60Hz

** Product improvement is a continual process at Senva and product features and specification may change without prior notice. Refer to instructions that accompany the product for installation and wiring.*